

2 PART TENDER FOR Vertical Hood Biosafety Cabinet-Qty 08 Nos.

Tender Fee – Rs.300/-, EMD: Rs. 70,000/Cost of Tender: Approx. Rs. 35 Lakhs
Last date for Sale of Documents: 07-10-2019 till 14.00hrs
Last date for submission: 08-10-2019 till 14.00hrs
Due date for opening bids: 08-10-2019 at 14.30hrs

GENERAL CONDITIONS

(Tender documents consist of 15 pages, Pg. 1 to Pg.14 – Technical Bid, Pg. 15- Price Bid)

Important Instructions: The bids shall be enclosed in an envelope and sealed duly marked "Vertical Hood Biosafety Cabinet-Qty 08 Nos." Ref. No. INS/L-5429/2019-2020 (Y)"; addressed and to be mailed to "The Purchase Officer". The bids are liable to be rejected if the sealed envelope is not addressed to "The Purchase Officer" with Tender Ref. No. and Item Description. Offers delivered in person shall be deposited in the Tender Box Labelled as 'TENDER BOX FOR PURCHASE TENDER" kept in the Ground Floor, Reception at Administration Building. If the bids are sent through courier or mail, it should reach by submission Date and Time and inStem will not responsible for the delay.

Important instruction for the Tenderers: -

All tenders shall be made in ENGLISH only.

The details in regard to technical specification and other terms and conditions should be cogent and clear to the extent possible.

Sealed tenders are invited at Institute for Stem Cell Biology and Regenerative Medicine -inStem, National Centre for Biological Sciences, GKVK Post, Bellary Road, Bangalore – 560 065 under 2 cover system from reputed OEM (Original Equipment Manufacturer) or reputed Manufacturers / Authorised Dealers for Supply, Installation, Commissioning and Technical Support for the following: -

Vertical Hood Biosafety Cabinet-Qty 08 Nos.

The Technical and Financial / Price Bids shall be submitted simultaneously in two (2) cover (sealed) system. The proposals shall be evaluated in two stages: (1) Technical and (2) Price / Financial. Technical evaluation will be carried out and those Vendors who score minimum 75% will qualify for Price Bid opening. Thereafter, Financial Proposal shall be evaluated. The Commercially LOWEST BIDDER shall be the first preferred Vendor for award of Order.

- I) The EMD amount should be put in <u>first sealed cover Cover I</u>, and super scribed as <u>"Technocommercial Bid"</u> and should contain -
- 1. Acceptance of Technical specifications, Annexure- A (page 9) and terms and conditions. Tender document to be enclosed with Date, Signature and Seal in every Page.
- 2. Complete Technical details of the Instrument offered (Specifications, Technical Parameters, Advantages, etc.,)
- 3. Supplier profile & Schedule of Experience Annexure B
- 4. Supplier must describe in detail the technical support they will be able to provide in Bangalore. Only those companies will be considered who have engineers based in Bangalore who have been trained on the machines being quoted for, prior to the date of installation.
- 5. Suppliers must provide complete list of publications arising from use of their machines, in which the machines have been used for the applications listed. Enclose Data Sheet and Sample Analysis (if any)
- 6. Details of Warranty Services.
- 7. Details of "After Sales Service" and "Factory Trained Engineers" available in Bangalore.
- 8. Xerox copies of the Purchase Orders for having supplied similar Instruments in India.
- 9. Schedule of deviation from specifications / conditions Annexure C.





- 10. Any other information the bidder like to provide with Date, Signature and Seal (Annexures should be duly signed and filled with date wherever necessary) (Please attach additional sheet(s), wherever necessary)
- II) The <u>second sealed cover</u> Cover II super scribed <u>'Price Bid'</u> (page 15) should contain only rates (please attach additional sheet(s), wherever necessary) (should be duly signed with seal and filled with date wherever necessary)

THE ABOVE MENTIONED TWO COVERS SHALL BE SEALED ON THE OUTSIDE WITH WAX SEAL BEARING THE LOGO/NAME OF THE COMPANY SUBMITTING THE BID.

THESE TWO COVERS SHALL BE AGAIN PUT INTO A SINGLE WAX SEALED COVER super scribed "Vertical Hood Biosafety Cabinet-Qty 08 Nos." and should reach INSTEM on or before 08-10-2019 before 14.00 hrs". This should be addressed to the Purchase Officer, inStem, NCBS, GKVK Post, Bellary Road, Bangalore – 65. The Techno – Commercial Bid will be opened on 08-10-2019 at 14.30 hrs.

On the date of tender opening (i.e. on 08-10-2019), only the Techno-Commercial Bids shall be opened in the presence of attending tenderers.

The Technical and Financial / Price Bids shall be submitted simultaneously in two (2) cover (sealed) system. The proposals shall be evaluated in two stages: (1) Technical and (2) Price / Financial. The Technical and Financial / Price Bids shall be submitted simultaneously in two (2) cover (sealed) system. The proposals shall be evaluated in two stages: (1) Technical and (2) Price / Financial. Technical evaluation will be carried out and those Vendors who score minimum 75% and above will qualify for Price Bid opening. Thereafter, Financial Proposal shall be evaluated. The Commercially LOWEST BIDDER shall be the first preferred Vendor for award of Order.

Earnest Money Deposit shall be submitted along with the "Techno-Commercial Bid" in the form of a Demand Draft drawn in favor of "Institute for Stem Cell Biology and Regenerative Medicine, payable at Bangalore" and the DD should be from a Commercial Bank/ Foreign Bank (First class Bank). Alternatively, a Bank Guarantee from a Commercial Bank/ Foreign Bank (First class Bank) may be provided (no other mode of payment will be accepted). The Bank Guarantee should be valid for 6 months from the date of opening. Bids not accompanied with Earnest Money Deposit shall be rejected. The EMD shall be refunded to the unsuccessful bidders once the order is released on the successful bidder.

The Techno-Commercial bids shall be evaluated subsequently and only the shortlisted firms Price Bid will be opened.

- 1.1 Quotations must be submitted giving complete details using enclosed tender papers.
- 1.2 The rates quoted should remain valid for a period of 180 days from the date of Price Bid opening.
- 1.3 Each page of the tender except the Price & Delivery part shall be on printed letterheads or forms and bear the signature, date, name and designation of the person signing the offer. If they are not on letterheads, a rubber stamp indicating full name, address and phone No., Telex No., Fax No. etc. of the firm shall be affixed at the end of each page. The price & delivery part shall be as Annexure B attached.
- 1.4 This tender document is not transferable. Only the party to whom the tender documents have been issued shall be entitled to quote.
- 1.5 Bids containing erasures or alterations are liable to be rejected unless countersigned by the Authorised signatory.





- 1.6 All rates and total amount should be written both in figures and in words and if there is any discrepancy between the two, the lowest amount only will be considered.
- 1.7 Tenders will be opened in the presence of attending tenderers on 08-10-2019 at 14.30 hours. In the event the due date is declared as holiday, the tender will be opened on the following working day.
- 1.8 If the item offered is to be imported, arrangements for import will be made by the Institute. Import duty and customs clearance will be under purchaser's scope.
- 1.9 We reserve the right to place order for part/reduced quantity than what is specified in the tender and also reserve the right to split the order to more than one supplier.
- 1.10 Any deviation/substitution in regard to the technical specification must be indicated in Annexure C of this tender document. Otherwise it shall be binding on the bidder to supply the items as specified in this tender specification.
- 1.11 All bids are to be submitted before the due date and time. The bids shall be enclosed in an envelope and sealed duly marked "Vertical Hood Biosafety Cabinet-Qty 08 Nos."; Ref. No. INS/L-5429/2019-2020 (Y)"; and mailed to the Purchase Officer. Offers delivered in person shall be deposited in the Tender Box kept in the office. Due date for opening the bids: 08-10-2019 (14.00 hours).
- 1.12 Please return the tender papers including Conditions of Tender as well as the Annexures with your signature, rubber stamp and date affixed on each page.
- 1.13 All bids in response to this invitation of tender should be submitted in a manner and method specified above. Tender which do not comply with the above conditions are liable to be rejected.
- 1.14 Late and delayed tenders will not be considered. Therefore, tenderers shall ensure that the tender reaches the Purchaser on or before the due date and time stipulated for receipt of bids.


TENDERS RECEIVED LATE OR AFTER THE DUE DATE WILL NOT BE CONSIDERED. INSTEM RESERVES THE RIGHT TO ACCEPT, REJECT ANY OR ALL TENDERS WITHOUT ASSIGNING ANY REASONS THERE OF.

- 1.15 Individuals signing the bid form and other supporting documents must specify the capacity in which they sign, like
 - a) Whether signing as a Sole Proprietor of the firm or his attorney.
 - b) Whether signing as a partner of the firm or his attorney
 - c) Whether signing for the firm as Agent.
 - d) Whether signing as Director of a Limited Company.

2. <u>CATALOGUE/TECHNICAL LITERATURE</u>

All necessary catalogue/drawing literature/data and details of item/s as are considered to be essential for full and correct evaluation of the bid shall invariably accompany the bid.







3. <u>BID GUARANTEE / EARNEST MONEY DEPOSIT: -</u> Bid Guarantee amount details are as below: -

Sl. No.	Item Description	BGA/EMD Amount	
1.	Vertical Hood Biosafety Cabinet-Qty 08 Nos	INR 70,000/-	1

The EMD/BGA shall be submitted by a DD (for outstation firms) or Banker's cheque (in case of local firm) from a Commercial Bank/ Foreign Bank (First class Bank) along with the bid, drawn in favor of "Institute for Stem Cell Biology and Regenerative Medicine, Bangalore". Alternatively, the EMD amount may be submitted by way of Bank Guarantee from a Commercial Bank/ Foreign Bank (First class Bank) valid for 6 months (no other mode of payment will be accepted). The BGA amount will be forfeited if the successful bidder fails to accept the Letter of Intent/ Purchase order or withdraws or amends, impairs or derogates from the tender in any respect within the period of validity of this tender. The offers are liable to be rejected, at the discretion of the Centre, if they are not accompanied with BGA. No interest shall be payable by INSTEM for BGA amount. The BGA shall be refunded to the unsuccessful bidders once the order is released on the successful bidder.

4. AUTHORITY OF AGENTS

In case where a bid is submitted by an Indian Agent on behalf of his foreign principal, such bid should be supported with a letter of Authority from the principal that the Indian Agent has been authorised to submit the bid on behalf of the principal. The indigenous manufacturers shall submit their bids directly.

5. PRICE

The tender to be quoted in foreign currencies & any other currencies approved/traded by RBI-USD/Euro/JPY/GBP/SGD/CAD/INR. The price/s quoted shall be firm till the complete execution of the order. All details relating to price, price breakup, inland transportation, documentation, taxes and duties, levies, Road/AIR/Marine freight charges, delivery terms (exworks/F.O.R/F.O.B/CIP) mode of payment, mode of Dispatch, Insurance, Agency Commission, if any, should be clearly stated. For indicating the price, the tenderers may choose any/all of the following:

- a) Ex-works (all other charges to be indicated separately).
- b) F.O.R. site (i.e. Freight, Packing & Forwarding, loading on to the transport, documentation etc. included.) Internal transportation, Freight, Insurance, etc. to be shown separately.
- c) F.O.B (cost of goods, Packing & Forwarding, Inland Transportation, Documentation, etc. till the item is loaded on to the cargo carrier). Freight & Insurance charges to be separately indicated.
- d) CIP (cost of goods, packing & forwarding, documentation, freight, insurance, etc. all included). However, freight & insurance charges to be indicated separately.
 - INSURANCE TO BE COVERED TILL inStem STORES.
- 6. The taxes (State, Central, Turnover tax, Works Contract Tax, etc.). Please specify which are applicable. The duties and other levies, freight, insurance shall be stated clearly and separately. Also please mention whether the same is included in the price/s quoted.

7. <u>VALIDITY OF BIDS</u>

The bids should be valid for a period of 180 days from the date of opening of the Price bids. Bids with shorter validity period are liable for rejection.



Page 4 of 15



Ref: INS/L-5429/2019-2020(Y)

Tender Notice No.005/2019-2020

8. DELIVERY

The tenderer should clearly mention the time required for supplying the item. The period of delivery will be counted (a) from the date of receipt of the order in case of Indian supplier and (b) from the date of opening of letter of credit/receipt of order (in the case of sight draft/advance draft) for foreign suppliers. The delivery date is the date at which the equipment should be delivered at INSTEM.

9. PACKING

The item should be packed appropriately so that it can sustain transit hazards, multiple landing, warehousing, etc. during transit.

10. PLACE OF DELIVERY

In the case of items indigenously manufactured, ALL DELIVERIES shall be effected to the Institute for Stem Cell Biology and Regenerative Medicine, National Centre for Biological Sciences, GKVK, Bellary Road, Bangalore-560065, whereas the foreign suppliers shall effect delivery up to Bangalore Airport, India by AIR only unless otherwise specified.

11. GUARANTEE/WARRANTY

The item/s covered under this tender shall be subject to a guarantee for trouble free performance, workmanship, material etc., fulfilling the specifications mentioned in this tender for min. 36 months from the date of commissioning. If any defect is found in the material, workmanship or performance during the guarantee period the same may either be repaired/replaced by the supplier as the case may be free of charge. The guarantee period for replacement of parts or repair work shall be same as above. A guarantee certificate to this effect should be forwarded to us with your invoice. For order placed on foreign suppliers, the supplier shall specifically confirm that their Indian representatives, if any, will provide with after sales service and will attend to any repairs or technical problems that may arise.

12. PERFORMANCE B/G

The successful bidder shall have to execute a performance B/G in accordance with the guarantee/warranty for 10% value of the order. This B/G has to be executed on an appropriate value of stamp paper in terms of a bank guarantee drawn on any Nationalized Bank or first class Foreign Bank and shall remain valid till the completion of the Defect Liability period/warranty period, with 6 months claim period.

13. TAXES AND DUTIES

The Centre shall deduct all taxes and duties, as applicable, from time to time from the bills payable.

14. PAYMENT TERMS

As per our Centre, 90% of the payment shall be made through Sight Draft (documents through bank) and balance 10% payable after installation, trail run and subject to acceptance by the group head through SAI and all other relevant documents, with Performance Bank Guarantee. All claims shall cease as per the Limitation Act.

15. CLARIFICATIONS

After opening the bids, if it becomes necessary for the purchaser to seek clarifications from the bidders, the same will be sought from the bidders. In such an event, the bidders will furnish all technical information / clarifications to the purchaser to reach on or before the due date fixed for that purpose, indicating the Purchaser's tender reference. If the technical clarifications





sought do not reach on or before the date fixed, the bids shall be summarily rejected without any further notice.

RISK CLAUSE

Notwithstanding the other terms therein, the Centre at its option will be entitled to terminate the contract and to avail from elsewhere; at the risk and cost of contractor; either the whole of the contract or any part which the contractor has failed to perform within the time stipulated or if the same performance is not available, the best and the nearest available substitute thereof. The contractor shall be liable for any loss which the Centre may sustain by reason of such risk contract in addition to penalty.

17. DISPUTE AND RESOLUTION

Any dispute or differences between the parties that cannot be settled by mutual discussion at appropriate levels shall be referred to the sole arbitration of the Director, INSTEM or his nominee and his decision in the matter shall be final and binding upon the parties to the dispute. The venue of arbitration proceedings shall be Bangalore. In respect of any matters pertaining to such arbitration, the courts of law in Bangalore will have exclusive jurisdiction.

18. OTHER TERMS

- a) If electrical/ AC/ technical works contract, appropriate license defining the required expertise from the approved Licensing authority.
- b) The Centre, will at its discretion ask for a solvency certificate from your bankers.

19. DEFINITION AND MEANINGS

In constructing these conditions, specifications, etc. in the tender document or the Annexures/Appendices the following words shall mean herein assigned definitions except where the subject context is otherwise stated.

PURCHASER:

Shall mean the Institute for Stem Cell Biology and

Regenerative Medicine

BID/TENDER:

Shall mean the proposal/document that the BIDDER

submits in the requested and specified form or otherwise

along with Annexures, Appendices, etc.

BIDDER/TENDERER:

Shall mean the firm/party who quotes against an enquiry.

CONTRACTOR/SUPPLIER:

Shall mean the party to whom a Work Order/Purchase Order is awarded to undertake all or a part of the work covered by this tender document as well as an amendment orders relating to this tender issued by the Purchaser and shall include his/their legal representative, assignee/s or

successor/s.

CONTRACT:

Shall mean and include the articles of agreement, Declaration form, the general and special conditions, the

Sten



Annexures, the Schedule of Quantities & rates and the specifications attached hereto and the drawings, if any.

ORDER VALUE:

Shall mean total value of the Purchase Order/Work order issued against this tender item including taxes, levies, etc.

20. <u>TECHNICAL SPECIFICATIONS</u> See Annexure – 'A'

- 21. For imported items, final price after totaling the prices of the individual items has to be mentioned with estimated freight, insurance, agency commission charges, etc. The price shall be FOR CIF BANGALORE AIRPORT.
- 22. INSTEM reserves the right to split the quantities or reject one or more offers in full or part without any reasons. Therefore, INSTEM decision is final and binding.
- 23. The quantity mentioned in the tender may be decreased/increased while ordering. However, the price quoted should be firm irrespective of change in the quantity.

24. ACCEPTANCE OF TENDERS

INSTEM does not pledge itself to accept the lowest/ any tenders and reserves to itself the right to accept the whole or part of the tenders or a part of the quantity offered.

- 25. The firm may quote in Foreign Currency for direct import on CIF basis as well as in Rupees on FOR INSTEM basis for local supply. Please indicate insurance, freight and other charges separately for direct import.
- 26. Your Service Engineer should be fully trained to install the equipment and capable of maintaining the equipment during / after the warranty period.

27. LIQUIDATED DAMAGES:

The successful bidder will have to agree that in case the item is not supplied within the agreed delivery schedule and after a grace period of seven days, then Liquidated Damages (not in terms of penalty) will be imposed automatically and be deducted from their bill at the rate of 0.5% per week subject to a maximum of 10% of the order value.

- 28. Micro and Small Enterprises (MSEs):
- a. Micro and Small Enterprises (MSE) must, along with their offer, provide proof of their being registered as MSE (indicating the terminal validity date of their registration) for the item tendered, with any agency mentioned in the notification of the Ministry of Micro, Small and Medium Enterprises (Ministry of MSME)
- b. The MSEs are exempted from payment of earnest money and tender fees subject to furnishing of relevant valid certificate for claiming exemption as per privilege rules of Government of India.
- c. The bidder submits registration of Udyog Adhar Memorandum (UAM) by Ministry of Micro Small and Medium Enterprises (MSME) vendors on Central Public Procurement Portal (CPPP). The bidders who





fail to submit UAM number shall not be able to avail the benefits available to MSEs as contained in Public Procurement Policy for MSEs Order 2012 issued by MSME.

Since INSTEM is a Public Funded Research Organisation, registered under Government of India Notification No.51/96 – Customs and 10/97 – for Central Excise is applicable for the items listed in the notification.

For and on behalf of Institute for Stem Cell Biology and Regenerative Medicine

Purchase Officer

GKVK Post, Bellary Road, Bangalore 560 065. India Phone +91-80-23666343 /344/345/346 . Telefax +91-80-23636662 purchase@ncbs.res.in . www.ncbs.res.in

ANNEXURE-A-SPECIFICATIONS

Vertical Hood Biosafety Cabinet-Qty 08 Nos.

TECHNICAL SPECIFICATIONS:

Specifications of Vertical Hood Biosafety Cabinet-Qty 08 Nos.

- The Bio safety cabinet should be Type A2 in which 70% Air should be re-circulated and 30% of the air should be exhausted
- The Bio Safety Cabinet must include two DC motors. High power consuming AC motors should not be used
- The motor must automatically adjust the airflow speed without the use of a damper to ensure continuous safe working conditions, even without maintenance adjustment
- In order to preserve safety to the user and the environment, the exhaust blower on the cabinet must continue operating when the supply blower stops working. If the exhaust blower should fail, the supply filter will also be turned off.
- In order to ensure consistent and reliable down flow velocity across the supply HEPA filter over the life of the cabinet, the cabinet must use a pressure sensor (rather than anemometer) to detect pressure drop across the supply filter, rather than in just one point across the down flow. The pressure sensor must be encased in order to protect the sensor from temperature, humidity and other environmental phenomena that can impact the sensor's performance
- The microprocessor must display the inflow and down flow air velocities in real-time on an LED display to ensure
 the user knows whether or not the cabinet is working under safe operating conditions.
- The front window must be a 10" sash opening and be made of laminated safety glass to ensure containment of
 potentially hazardous samples in the case of accidental glass breakage.
- All interior and exterior parts must be painted or smooth to ensure no risk of cuts to users or maintenance personnel.
- The front of the cabinet must be angled 10° to help minimize glare on the window to the user, and to ensure that the user's posture is comfortable during a working session. Inadequate user ergonomics in a safety cabinet may lead to excessive fatigue, unsafe working habits and harmful consequences to user safety or product contamination.
- The cabinet noise level must be less than 63 dB(A) for a 4 foot cabinet as measured in a sound proof room 12 inches in front of the cabinet and 15 inches above the work surface. Lower noise levels promote more comfortable and safer working habits of the user.
- The Biosafety Cabinet should have microprocessor controller and same must be located on a slanted front panel so it is easy to see and reach from a seated working position in front of the cabinet.
- The interior of the front window must be accessible for cleaning without requiring the user remove or support the window.
- The biological safety cabinet must be capable of achieving current state-of-the-art in energy efficiency. A biological safety cabinet with lights on and fan at operating speed should consume less than 200 watts for a nominal four foot width and have a reduced energy mode for non-operational maintenance on containment in the work area.
- The cabinet must automatically reduce fan/blower motor speed to 30% when the front window sash is in closed position to ensure reduced energy consumption when the cabinet is not in use.





- In order to provide maximum effectiveness, efficiency and safety to laboratory Personnel, UV light must be
 programmable to allow for specific exposure times from 0 to 24 hours. The automatic shut off feature on the UV
 light saves money on replacement of the bulbs.
- The Cabinet should have provision to fit taps for Vacuum, Water and Non Combustible Gas. Taps should be quoted
 as optional items
- The Bio Safety Cabinet should be NSF certified with listing on NSF website.
- The Bio safety cabinet should incorporate HEPA filter of the class H 14 EN 1822 or better and having minimum efficiency of 99.995% at 0.3 μm particle size.

Dimension:

- Exterior 1500 H x 1300 W x 800 D; Interior 800 H x 1200 W x 500 D
- Ventilation System Exhaust and Inflow air volume approx 300-350 CFM
- Heat Emissions at 25°C should be approx 0.2 KW or lesser.
- The Bidders should provide details of Standard Warranty available
- The cabinet Should be provided with Microprocessor controller and large LED display for inflow and Down flow air velocity and hours of operation, Audible and visual Alarms for HEPA filter failure, blower failure, airflow speed failure, Incorrect window position.
- The BSC must incorporate an LED Indicator to indicate filter loading and should provide visual and audible alarm to indicate excessive HEPA filters loading which can result in unsafe airflows deviation from the NSF recommended inflow and down flows air velocity values measured in meters per second or foot per minute.
- The cabinet should be provided with fixed / adjustable Height Stand, UV Light and one set of detachable arms rest and one / two electrical outlet.
- The Drain Pan of the BSC should be made of Stainless Steel. The drain pan should not be painted or power coated.
- The Bio safety cabinet should have dual side wall with negatively pressurized interstitial space.
- 3 Years Warranty from the date of Installation.





INFORMATION TO TENDERERS

The Tender shall be evaluated under 2 (Two) Bid System

- I Technical Bid
- II Financial Bid

TECHNICAL SPECIFICATIONS & EVALUATION CRITERIA WITH MARKS FOR 2 PART TENDER FOR "Vertical Hood Biosafety Cabinet-Qty 08 Nos".

	TECHNICAL EVALUATION CRITERIA WITH MARKS	
SI No.	Technical Requirement	Marks
1	The Bio safety cabinet should be Type A2 in which 70% Air should be recirculated and 30% of the air should be exhausted The Bio Safety Cabinet must include two DC motors. High power consuming AC motors should not be used	
2	The motor must automatically adjust the airflow speed without the use of a damper to ensure continuous safe working conditions, even without maintenance adjustment. In order to preserve safety to the user and the environment, the exhaust	
	blower on the cabinet must continue operating when the supply blower stops working. If the exhaust blower should fail, the supply filter will also be turned off.	
3	In order to ensure consistent and reliable down flow velocity across the supply HEPA filter over the life of the cabinet, the cabinet must use a pressure sensor (rather than anemometer) to detect pressure drop across the supply filter, rather than in just one point across the down flow. The pressure sensor must be encased in order to protect the sensor from temperature, humidity and other environmental phenomena that can impact the sensor's performance	10
	The microprocessor must display the inflow and down flow air velocities in real-time on an LED display to ensure the user knows whether or not the cabinet is working under safe operating conditions.	
4	The front window must be a 10" sash opening and be made of laminated safety glass to ensure containment of potentially hazardous samples in the case of accidental glass breakage. All interior and exterior parts must be painted or smooth to ensure no risk of	10
	cuts to users or maintenance personnel. The front of the cabinet must be angled 10° to help minimize glare on the window to the user, and to ensure that the user's posture is comfortable	
	during a working session. Inadequate user ergonomics in a safety cabinet may lead to excessive fatigue, unsafe working habits and harmful consequences to user safety or product contamination.	
5	The cabinet noise level must be less than 63 dB(A) for a 4 foot cabinet as measured in a sound proof room 12 inches in front of the cabinet and 15 inches above the work surface. Lower noise levels promote more comfortable and safer working habits of the user.	10
	The Biosafety Cabinet should have microprocessor controller and same must be located on a slanted front panel so it is easy to see and reach from a seated working position in front of the cabinet. The interior of the front window must be accessible for cleaning without requiring the user remove or support the window.	
6	The biological safety cabinet must be capable of achieving current state-of-the-art in energy efficiency. A biological safety cabinet with lights on and fan	10







	at operating speed should consume less than 200 watts for a nominal four	
	on containment in the work area.	,
	The cabinet must automatically reduce fan/blower motor speed to 30% when	
	the front window sash is in closed position to ensure reduced energy	
	consumption when the cabinet is not is use.	
	In order to provide maximum effectiveness, efficiency and safety to	
	laboratory Personnel, UV light must be programmable to allow for specific	
	exposure times from 0 to 24 hours. The automatic shut off feature on the UV	
	light saves money on replacement of the bulbs.	
7	The Cabinet should have provision to fit taps for Vacuum, Water and Non	10
1 '	Combustible Gas. Taps should be quoted as optional items	10
	The Bio safety Cabinet should be NSF certified with listing on NSF website.	
	The Bio safety Cabinet should be NSF certified with fisting on NSF website.	
1	The Bio safety cabinet should incorporate HEPA filter of the class H 14 EN	
	1822 or better and having minimum efficiency of 99.995% at 0.3 μm particle	
	size.	
1	Dimension	
	Exterior 1500 II v 1200 W v 900 D. Interior 900 II v 1200 W v 500 D	
	Exterior 1500 H x 1300 W x 800 D; Interior 800 H x 1200 W x 500 D	
	Ventilation System Exhaust and Inflow air volume approx 300-350 CFM	
8	Heat Emissions at 25°C should be approx 0.2 KW or lesser.	8
	The Bidders should provide details of Standard Warranty available	
	The cabinet Should be provided with Microprocessor controller and large	
	LED display for inflow and Down flow air velocity and hours of operation,	
	Audible and visual Alarms for HEPA filter failure, blower failure, airflow	
	speed failure, Incorrect window position.	
1	The BSC must incorporate an LED Indicator to indicate filter loading and	
	should provide visual and audible alarm to indicate excessive HEPA filters	
	loading which can result in unsafe airflows deviation from the NSF	
	recommended inflow and down flows air velocity values measured in meters	
	per second or foot per minute.	
9	The cabinet should be provided with fixed / adjustable Height Stand, UV	10
	Light and one set of detachable arms rest and one / two electrical outlet.	***
	The Drain Pan of the BSC should be made of Stainless Steel. The drain pan	
	should not be painted or power coated.	
	The Bio safety cabinet should have dual side wall with negatively	
	pressurized interstitial space.	
1	3 Years warranty from the date of Installation	
	Total	100
	iviai	100

Evaluation will be carried out and those Vendors who score minimum 75% will qualify for Price Bid opening. Thereafter, Financial proposal shall be evaluated. The Commercially LOWEST BIDDER shall be the first preferred Vendor for award of Order.





ANNEXURE – B SCHEDULE OF EXPERIENCE

Please furnish list of major supplies/works undertaken in relevant to this tender during the past two years.

two y	ears.				
SI.	Name of the company	Name of	Purchase Order	Brief description	Value (Rs.)
No.	with full address	project	No. & date		
					*
Signa	iture				
Name	2				
rann					
Desig	gnation				
Nam	e of company				
Dets					
Date					
Seal of the company					





ANNEXURE - C

SCHEDULE OF DEVIATION FROM SPECIFICATIONS/CONDITIONS

All deviations from the specifications/conditions shall be filled in by the bidder in this schedule.					
×					
The bidder hereby certifies to of this tender. [State NIL if	hat the above mentioned are the	e only deviations from Te	chnical Specification		
Signature Signature	no deviation is envisaged.				
Name					
Designation	,				
Name of the company		•			
Date					
Seal of the company					
coar of the company					





<u>COVER – II PRICE BID</u>

Vertical Hood Biosafety Cabinet-Qty 08 Nos.

Sl. No.	Item Description	Qty	Unit Price	Total Price
181				

Please enter Unit Price, Total Price and Grand Total in figures as well as words. Unit price and Total Price may be entered below each item.

